



**Always a
step ahead!**

Accessories fcf'GD9K 9'(- \$; HI&(

Glow-wire hang-mounted cutth]b['XYj]W'GD9K 9'(- \$; HI&(

Accessories included

Replacement wire
Spool with 0.65 mm / 9 m wire



Flat nose pliers



Spare fuses



Flat spanner



The product

The handy, lightweight glow-wire hang-mounted cutting device SPEWE 490GT is an ideal second device or for smaller order volumes. It can be used universally as tabletop model or with the bracket as hang-mounted device on the building scaffolding. The free passage along the scaffold is ensured, and the device can be quickly relocated without any time-consuming fastening of screws. No warm-up time, immediately ready for use.

Technical Data

- Plate thickness: 240 mm
- Cut length: 1040 mm
- Weight incl. transformer: 7.3 kg

Scope of delivery

The hang-mounted cutting device SPEWE 490GT incl. transformer, replacement wire 0.65 mm / 9 m, flat nose pliers, spare fuses, flat spanner. Delivered in box.

GdYk Y'5;
Hauptstrasse 332
CH-5326 Schwaderloch

Phone: +41 (0)56 203 03 30
Fax: +41 (0)56 203 03 31
E-mail: info@spewe.ch
Website: www.spewe.ch



Convincing details



Alternative set-up positions



- 1 The push-button ensures that the device is running only when it is really needed. It is immediately ready for use without a warm-up period
- 2 Integrated safety transformer with fuse for high cutting performance
- 3 Swivelling cutting arm with ball guides
- 4 Mitre slider (positioning aid) at the bottom for repeat cuts
- 5 Tie-down strap (working angle can be individually adjusted)
- 6 Continuously adjustable position-holder for bevel cuts
- 7 Bearing rail with board guide
- 8 Back railing anchorage fixed in place for fast vertical mounting on the scaffolding
- 9 Assembled hanging on the scaffolding
- 10 Assembled vertically on the scaffolding
- 11 Laid down as tabletop model on a stack of boards

Types of cut

